



Max. strain		Light	Small	Large	XL	X ² L	X ³ L	X ⁴ L
Pull & Push	daN	500	2.000	2.000	5.000	10.000	15.000	20.000
Bending moment	Nm	10.000	10.000	10.000	25.000	50.000	100.000	150.000

Measurements		Light	Small	Large	XL	X ² L	X ³ L	X ⁴ L
A	mm	80	80	80	80	120	120	120
B	mm	230	230	230	-	-	-	-
C	mm	186	186	186	-	-	-	-
D	mm	250	250	250	Ø 310	Ø 400	Ø 560	Ø 750
E	mm	206	206	206	Ø 250	Ø 340	Ø 500	Ø 670
F	mm	-	-	-	Ø 100	Ø 140	Ø 200	Ø 270
H	mm	30	30	30	30	40	50	60

Anchor bolts		Light	Small	Large	XL	X ² L	X ³ L	X ⁴ L
Bolt size	mm	M 16	M 16	M 16	M 16	M 20	M 24	M24
Number of bolts	pcs	4	4	4	12	12	12	14
Max. tensile force per bolt	daN	250	600	600	500	900	1.200	1.300
Max. shear force per bolt	daN	600	1.000	1.000	700	1.250	1.800	2.000

Applications: Adapter for tracks & profiles. Stepless adjustment for **highest flexibility**

